

# MATERIAL SAFETY DATA SHEET

358 0507A

## EPS Primer – Part A



### SECTION 1: IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY

Product Name: **EPS PRIMER – PART A**  
 Company Name: Polycote UK  
 Centre Point • Wolseley Road  
 Woburn Road Industrial Estate  
 Kempston • Beds MK42 7EF  
 Telephone Number: 01234 846400

### SECTION 2: HAZARDS IDENTIFICATION

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects:

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Label elements under CLP:

Hazard statements: H226: Flammable liquid and vapour.  
 H315: Causes skin irritation.  
 H317: May cause an allergic skin reaction.  
 H319: Causes serious eye irritation.  
 H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning



Hazard pictograms: GHS02: Flame  
 GHS05: Corrosion

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241: Use explosion-proof electrical/ventilating/lighting/equipment.  
 P280: Wear protective clothing.  
 P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Other hazards: In use, may form flammable / explosive vapour-air mixture.  
 PBT: This substance is not identified as a PBT/vPvB substance.

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients:

Einecs	CAS	PBT/WEL	CLP Classification	Percent
XYLENE				
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox 4: H332; Acute Tox 4: H312; Skin Irrit. 2: H315	10-30%
BISPHENOL A-(EPICHLORHYDRIN) (REACTION PRODUCT)				
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
4-METHYLPENTAN-2-ONE				
203-550-1	108-10-1	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335 -: EUH066	10-30%
BUTAN-1-OL				
200-751-6	71-36-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE3: H336	1-10%

Einecs	CAS	PBT/WEL	CLP Classification	Percent
ETHYLBENZENE				
202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1-10%

### SECTION 4: FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.  
 Eye contact: Bathe the eye with running water for 15 minutes.  
 Ingestion: Wash out mouth with water.  
 Inhalation: Consult a doctor.  
**Most important symptoms and effects, both acute and delayed**  
 Skin contact: There may be mild irritation at the site of contact.  
 Eye contact: There may be irritation and redness.  
 Ingestion: There may be irritation of the throat.  
 Inhalation: No symptoms.  
 Delayed / immediate effects: Immediate effects can be expected after short-term exposure.  
 Immediate / special treatment: Not applicable.

### SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.  
 Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.  
 Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.  
 Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.  
 Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### SECTION 7: HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.  
 Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.  
 Suitable packaging: Must only be kept in original packaging.  
 Specific end use(s): No data available.

**Polycote EPS Primer – Part A Cont.**

358 0507A

**SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION****Hazardous ingredients:**

XYLENE

Workplace exposure limits:		Respirable dust	
8 hour TWA:	15 min. STEL:	8 hour TWA:	15 min. STEL:
UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	–

4-METHYLPENTAN-2-ONE

UK	208 mg/m <sup>3</sup>	416 mg/m <sup>3</sup>	–
----	-----------------------	-----------------------	---

ETHYLBENZENE

UK	441 mg/m <sup>3</sup>	552 mg/m <sup>3</sup>	–
----	-----------------------	-----------------------	---

BUTAN-1-OL

UK	–	154 mg/m <sup>3</sup>	–
----	---	-----------------------	---

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

**SECTION 9: PHYSICAL & CHEMICAL PROPERTIES**

State:	Liquid
Colour:	Red
Odour:	Characteristic odour
Solubility in water:	Slightly soluble
Also soluble in:	Most organic solvents
Viscosity:	Viscous
Boiling point/range°C:	116
Flash point°C:	14
Relative density:	1.09

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity:	Stable under recommended transport or storage conditions.
Chemical stability:	Stable under normal conditions. Stable at room temperature.
Hazardous reactions:	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.
Conditions to avoid:	Heat. Hot surfaces. Sources of ignition. Flames.
Materials to avoid:	Strong oxidising agents. Strong acids.
Haz. decomp. products:	In combustion emits toxic fumes.

**SECTION 11: TOXICOLOGICAL INFORMATION****Hazardous ingredients:**

XYLENE

ORL	MUS	LD50	2119 mg/kg
ORL	RAT	LD50	4300 mg/kg
SCU	RAT	LD50	1700 mg/kg

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600 mg/kg
ORL	RAT	LD50	11400 mg/kg
SKN	RBT	LD50	>20 ml/kg

4-METHYLPENTAN-2-ONE

IPR	RAT	LD50	400 mg/kg
ORL	MUS	LD50	1900 mg/kg
ORL	RAT	LD50	2080 mg/kg

ETHYLBENZENE

IPR	MUS	LD50	2624 µl/kg
ORL	RAT	LD50	3500 mg/kg

BUTAN-1-OL

IVN	RAT	LD50	310 mg/kg
ORL	MUS	LD50	2680 mg/kg
ORL	RAT	LD50	790 mg/kg

**Relevant effects for mixture:**

Effect	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

**Symptoms / routes of exposure**

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed/immediate effects: Immediate effects can be expected after short-term exposure.

**SECTION 12: ECOLOGICAL INFORMATION**

Persistence and degradability:	Biodegradable.
Bioaccumulative potential:	No bioaccumulation potential.
Mobility:	Readily absorbed into soil.
PBT identification:	This substance is not identified as a PBT/vPvB substance.
Other adverse effects:	Negligible ecotoxicity.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal company.
Recovery operations:	Use principally as a fuel or other means to generate energy.
Waste code number:	08 04 09
Disposal of packaging:	Normally this resin material will be mixed in its own pot with its hardener. When this is done the resultant material in the pot is inert and the label must be defaced and pot and remnant may be disposed of as normal industrial waste. Empty packaging contaminated with residues of hazardous substances are classified with waste code number 15-01-10 (plastic and metal).
NB:	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14: TRANSPORT INFORMATION**

UN number:	UN1866
Shipping name:	RESIN SOLUTION (XYLENE; 4-METHYLPENTAN-2-ONE; BUTAN-1-OL)
Transport class:	3
Packing group:	II
Environmentally hazardous:	No
Marine pollutant:	No
Special precautions:	No special precautions.
Tunnel code:	D/E
Transport category:	2

**SECTION 15: REGULATORY INFORMATION**

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Polycote UK**

Centre Point • Wolseley Road • Woburn Road Industrial Estate  
Kempston • Beds • MK42 7EF  
Technical Helpline: 01234 846400

**POLYCOTE®**  
"maintenance made easy"

**SECTION 16: OTHER INFORMATION**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

Phrases used in s.2 and 3:

EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

The Safety Data above is applicable to the product only as used according to the purposes and methods described on the relevant Technical Data Sheet, available from Polycote UK on request.

The information above is based on our present knowledge and is believed to be correct but does not purport to be all inclusive and should only be used as a guide. No warranty is implied with respect to the specification of the product. It is intended to describe the product solely in terms of its safety requirements and relates only to the specific material designed and may not be valid for such material used in combination with any other materials or in any process. This data does not constitute the users own assessment of workplace risk as required by other Health and Safety legislation, nor is it a sales specification or indication of suitability for any particular use. The user must satisfy himself as to the suitability of the product for his purpose. No legally valid contractual relationship is established by the above data, and Polycote UK shall not be held liable for any damage resulting from handling or from contact with the above product.

Date of Issue: August 2018

**Polycote UK**

Centre Point • Wolseley Road • Woburn Road Industrial Estate  
Kempston • Beds • MK42 7EF  
Technical Helpline: 01234 846400

# MATERIAL SAFETY DATA SHEET

358 0507B

## EPS Primer – Part B



"maintenance made easy"

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY

Product Name: **EPS PRIMER – PART B**  
 Company Name: Polycote UK  
 Centre Point • Wolseley Road  
 Woburn Road Industrial Estate  
 Kempston • Beds MK42 7EF  
 Telephone Number: 01234 846400

### SECTION 2: HAZARDS IDENTIFICATION

Classification under CLP: Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315  
 Most important adverse effects:

Flammable liquid and vapour. Causes skin irritation. Causes serious eye damage.

#### Label elements under CLP:

Hazard statements: H226: Flammable liquid and vapour.  
 H315: Causes skin irritation.  
 H318: Causes serious eye damage.

Signal words: Danger



Hazard pictograms: GHS02: Flame  
 GHS05: Corrosion

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.  
 P280: Wear eye protection.  
 P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Other hazards: Causes burns. Irritating to skin. Risk of serious damage to eyes.

PBT: This substance is not identified as a PBT/vPvB substance.

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

#### Hazardous ingredients:

Einecs	CAS	PBT/WEL	CLP Classification	Percent
<b>POLYAMINOAMIDE ADDUCT</b>				
-	-	-	Eye Dam. 1: H318	50 - 70%
<b>XYLENE – REACH registered number(s): 01-2119488216-32</b>				
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox 4: H332; Acute Tox 4: H312; Skin Irrit. 2: H315	30 - 50%
<b>BUTAN-1-OL – REACH registered number(s): 01-2119484630-38</b>				
200-751-6	71-36-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE3: H336	1 - 10%
<b>ETHYLBENZENE</b>				
202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1 - 10%

### SECTION 4: FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.  
 Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.  
 Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.  
 Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

#### Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.  
 Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.  
 Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.  
 Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.  
 Delayed / immediate effects: Immediate effects can be expected after short-term exposure.  
 Immediate / special treatment: Eye bathing equipment should be available on the premises.

### SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.  
 Exposure hazards: In combustion emits toxic fumes.  
 Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing – see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.  
 Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.  
 Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### SECTION 7: HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.  
 Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.  
 Suitable packaging: Must only be kept in original packaging.  
 Specific end use(s): No data available.

**Polycote EPS Primer – Part B Cont.**

358 0507B

**SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION****Hazardous ingredients:**

XYLENE

**Workplace exposure limits:**

	8 hour TWA:	15 min. STEL:	Respirable dust	8 hour TWA:	15 min. STEL:
UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	–	–	–

ETHYLBENZENE

	8 hour TWA:	15 min. STEL:	8 hour TWA:	15 min. STEL:
UK	441 mg/m <sup>3</sup>	552 mg/m <sup>3</sup>	–	–

BUTAN-1-OL

UK	–	154 mg/m <sup>3</sup>	–	–
----	---	-----------------------	---	---

Engineering measures: Ensure there is sufficient ventilation of the area.  
Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.  
Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

**SECTION 9: PHYSICAL & CHEMICAL PROPERTIES**

State: Liquid  
Colour: Brown  
Odour: Perceptible odour  
Evaporation rate: Negligible  
Solubility in water: Slightly soluble  
Viscosity: Viscous  
Flash point: 23°C  
pH: 10

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity: Stable under recommended transport or storage conditions.

Stability: Stable under normal conditions.

Haz. reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

**SECTION 11: TOXICOLOGICAL INFORMATION****Hazardous ingredients:**

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

BUTAN-1-OL

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

**Relevant effects for mixture:**

Effect	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

**Symptoms:**

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed/immediate effects: Immediate effects can be expected after short-term exposure.

**SECTION 12: ECOLOGICAL INFORMATION**

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Mobility: Readily absorbed into soil.

Other adverse effects: Negligible ecotoxicity.

PBT identification: This substance is not identified as a PBT/vPvB substance.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: During the process of mixing this curing agent with its resin the container may be flushed with some of the mixed material rendering contents quickly inert. Once done the label should be defaced & container may now be disposed of as industrial waste. Empty packaging contaminated with residues of hazardous substances are classified with waste code number 15-01-10 (plastic and metal).

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14: TRANSPORT INFORMATION**

UN No: 1866

Shipping name: RESIN SOLUTION  
(XYLENE; POLYAMINOAMIDE ADDUCT;  
BUTAN-1-OL)

Transport Class: 3

Packing group: III

Environmentally hazardous: No

Marine pollutant: No

Tunnel code: D/E

Transport category: 3

**SECTION 15: REGULATORY INFORMATION**

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Polycote UK**

Centre Point • Wolseley Road • Woburn Road Industrial Estate  
Kempston • Beds • MK42 7EF

Technical Helpline: 01234 846400



"maintenance made easy"

**SECTION 16: OTHER INFORMATION**

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.  
This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

## Risk phrases used

in s.2 and s.3:

- H225: Highly flammable liquid and vapour.
- H226: Flammable liquid and vapour.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

The Safety Data above is applicable to the product only as used according to the purposes and methods described on the relevant Technical Data Sheet, available from Polycote UK on request.

The information above is based on our present knowledge and is believed to be correct but does not purport to be all inclusive and should only be used as a guide. No warranty is implied with respect to the specification of the product. It is intended to describe the product solely in terms of its safety requirements and relates only to the specific material designed and may not be valid for such material used in combination with any other materials or in any process. This data does not constitute the users own assessment of workplace risk as required by other Health and Safety legislation, nor is it a sales specification or indication of suitability for any particular use. The user must satisfy himself as to the suitability of the product for his purpose. No legally valid contractual relationship is established by the above data, and Polycote UK shall not be held liable for any damage resulting from handling or from contact with the above product.

Date of Issue: June 2017

**Polycote UK**

Centre Point • Wolsley Road • Woburn Road Industrial Estate  
Kempston • Beds • MK42 7EF  
Technical Helpline: 01234 846400