

# Flexiline Tack Coat

**Sprayable (Aerosol) Tack Coat  
to assist the application of Flexiline**



**“maintenance made easy”**



## DIRECTIONS FOR USE

### COVERAGE

10m<sup>2</sup> per can. This equates to 100 linear metres of 100mm line per can.

### STORAGE

Store the cans in a cool place out of direct sunlight and away from any sources of ignition, ideally between 5°C and 20°C. When stored under these conditions shelf life is 12 months.

## PRODUCT DESCRIPTION

**Flexiline is a road marking system based on pre-formed lines, symbols and letters manufactured from modified BS3262 thermoplastic. Flexiline Tack Coat is used to improve adhesion and create a tough, long lasting solution to linemarking.**

**TYPICAL USES** Flexiline Tack Coat is ideal where Flexiline is being applied to smooth or concrete surfaces

**COLOUR** Flexiline Tack Coat is clear when dry.

**PACKAGING** Flexiline Tack Coat is supplied in easy-to-use 750ml aerosol cans.

### SURFACE PREPARATION

Flexiline Tack Coat will not adhere to surfaces which are contaminated by loose debris, mud, oil, grease or where surface water is present. Sweep and clean the area thoroughly. Dry out any surface wetness using a gas torch.

If application is onto new asphalt, we advise that it is left for at least 6-8 weeks to settle.

If any doubt as to the substrate should arise, complete a test patch before continuing.

### APPLICATION

Shake can thoroughly for at least 90 seconds before use. Flexiline Tack Coat should be applied by simply spraying the surface that the Flexiline will be applied to.

### CURING TIMES

Touch dry: 5 minutes @ 15°C  
Walk on time: 10 minutes @ 15°C  
Traffic time: 20 minutes @ 15°C

## HEALTH & SAFETY

**Before using this product, please ensure you have received and read carefully both the Hazard Label applied to the container and the relevant Material Safety Data Sheets.**

## ANY QUESTIONS?

Please do not hesitate to contact us for advice regarding the use of this product or its suitability for your particular application. Our aim is to provide all the technical help you need to make an informed choice and achieve total success.

Polycote Technical Helpline  
**01234 846400**

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure for himself that the product is fit for the intended purpose and that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights and third parties are involved. In the light of the Company's policy of continual research and development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.