

Suregrip 500

Slip resistant treatment for all tile and stone surfaces



“maintenance made easy”



PRODUCT DESCRIPTION

A fantastic single pack water-based coating that is completely clear and will provide a slip resistant finish in one easy application.

Being water-based, Suregrip 500 is acid free, non-flammable, non-hazardous and is biodegradable.

Suregrip 500 is completely clear and will barely alter the appearance or nature of the surface and is suitable for both internal and external use.

TYPICAL USES

Suregrip 500 can be applied in a wide variety of areas including entrance halls, gyms, kitchens, swimming pool surrounds, shower units and indeed anywhere floors can become slippery, especially when wet.

SUITABLE SUBSTRATES

Suregrip 500 may be applied to concrete, marble, mineral surfaces, enamel, ceramic slabs and terrazzo tiles.

PACKAGING

Suregrip 500 is supplied in 1 and 2.5 litre containers and is a colourless liquid.

TECHNICAL DATA

- Physical state at 20°C – Liquid
- Appearance – Colourless
- Odour – Scented
- Boiling Point – 100°C
- Flash Point – N/A
- pH – 4 ± 0.5
- Density – 1.1 Kg/L
- Solubility in water (vol/vol) Fully soluble

DIRECTIONS FOR USE

APPLICATION

We recommend that you carry out a test first on a small area to ensure the finished result is acceptable.

Shake before use to obtain the best results. *Suregrip 500* is ready to use but can be diluted up to 1:1 with water.

Apply using a brush or low-pressure spray onto a clean and dry surface. Allow *Suregrip 500* to act for 40-60 mins. making sure it does not dry out during the application. When completed, rinse with water, after which the treated surface can be used immediately.

You may need to repeat the application, depending on the substrate and the resistance level to necessary scrubbing.

Do not use *Suregrip 500* on crystallized, marble or polished surfaces, and do not dilute or mix with any other product, other than water.

Important: This data sheet is compiled from our experiences of testing this product. We cannot be held liable for its use in individual cases. For more information, please see the Material Safety Data Sheet.

APPLICATION TEMPERATURE

Normal application temperature for *Suregrip 500* is between 5° and 30°C. Do not apply during rain, frost or in direct sun. Always use products in a well-ventilated space.

COVERAGE

The coverage of *Suregrip 500* is approximately 8 to 10m² per litre, depending on the texture and porosity of the surface.

CLEANING

Tools and equipment should be cleaned whilst resin is still wet using warm water. Hands and skin should be cleaned immediately with organic hand cleaner.

SHELF LIFE & STORAGE

Shelf life in unopened containers is approximately 24 months subject to conditions of storage. Store in a cool, dry, frost-free environment and away from sources of ignition.

ONGOING MAINTENANCE

To maintain the appearance and functionality of the non-slip treatment use *Suregrip 500* very diluted (20% *Suregrip 500* : 80% water).

HEALTH & SAFETY

Before using this product, please ensure you have received and read carefully both the Hazard Label applied to the container and the relevant Material Safety Data Sheets.

ANY QUESTIONS?

Please do not hesitate to contact us for advice regarding the use of this product or its suitability for your particular application. Our aim is to provide all the technical help you need to make an informed choice and achieve total success.

Polycote Technical Helpline
01234 846400

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure for himself that the product is fit for the intended purpose and that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights and third parties are involved. In the light of the Company's policy of continual research and development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.

REV: 02/12